

CLOSED ATTIC ASSEMBLY

NOTE: IN COLD CLIMATES, EMBED TOP CHORD METAL CONNECTOR PLATES IN SPF TO PREVENT WINTER-TIME CONDENSATION

SPRAY POLYURETHANE FOAM TO SPECIFIED THICKNESS

ROOF SHEATHING

TRUSS TOP CHORD OR RAFTER

CEILING / THERMAL BARRIER AS REQUIRED BY CODE

PROTECT SPF SURFACE FROM IGNITION AS REQUIRED BY CODE

NOTE: IN COLD CLIMATES USE CODE-APPROVED VAPOR RETARDER



DRAWN BY M.SAUCEDO	<h2>DEMILEC USA LLC.</h2> <p>SPRAY FOAM INSULATION ARCHITECTURAL DETAILS</p> <p>CLOSED ATTIC ASSEMBLY</p> <p><small>2925 GALLERIA DRIVE - ARLINGTON, Tx 76011 - Phone: (817) 640-4900 - Fax: (817) 633-2000 Website: www.DEMILECUSA.com - http://www.sealection500.com - E-mail: Info@DEMILECUSA.com</small></p>	SCALE N.T.S.
ARCH-51		SHEET NO. 1
DATE 11-24-2008		